CDE7520 Firmware Update Notice

Please check Build Number information first.

Path: Launcher \rightarrow Settings \rightarrow About

Weld	come	03 : 17 PM 2020.12.15 Tues	day			
	Browser	Display	EnterpriseAgent	Folders	Manager	Miracast
Rev	velDigital Pl	Settings	SureMDM Nix	WPS Office	vCastReceiver	vSweeper
						ViewSonic 🞎
Sett	ings					
	Network		Date & Time			
	Device					
	System					

If your build number is "CDE7520", please download firmware from "CDE7520 Main Firmware" download link (File name is : VIEWSONIC_BIAOPAI_W75PNA-BO9D86A-G_16G_MS8386_320W_5_2_2-stable_20211103_191906.zip)

Local system updates	
Online system updates	
Legal information	
Android version 8.0.0	
Kernel version 4.9.44	

If your build number "CDE7520_BE2", please download firmware from "CDE7520 (BE) Main Firmware" download link. (File name is : VIEWSONIC_BIAOPAI_W75PNA-BOP186A-G_16G_MS8386_320W_5_2_2-stable_20211103_195232.zip)

C	About				
	Local system updates				
	Online system updates				
	Legal information Android version 8.0.0				
	Kernel version 4.9.44				
	Build number ViewSonic/CDE7520_BE2/CDE7520_BE2:8.0.0/20201208.162308:userdebug/ release-keys				

CDE6520/7520/8620 FW upgrade instruction

1. Debug Menu Upgrade Procedure (recommend)

Tools:

- (1) USB disk (Format FAT32) * 1 PCS.
- (2) Remote controller * 1 PCS.

Procedure:

- (1) Format the USB disk as FAT32.
- (2) Extract upgrade file to the U disk (FAT32 format) in the root directory. You will get "upgrade_8386".
- (3) Insert USB disk into the USB port of the TV board.
- (4) Turn on the panel. Press "Input 991" with remote controller, and then the debug menu will pop up.
 Select Upgrade-> Upgrade All, press "Enter", and confirm.

2. Power Key Upgrade Procedure

Tools:

USB disk (Format FAT32) * 1PCS.

Procedure

- (1) Format the USB disk as FAT32.
- (2) Extract .zip file (after unzip you can found "upgrade_8386" folder) and copy "upgrade_8386" folder to U disk (FAT32) in the root directory.
- (3) Insert USB disk into the USB port of the TV board.
- (4) Press the POWER key to turn on the display and hold it for 6 seconds until the power LED twinkles in red and blue.
- (5) The display will upgrade first. When finished, the screen will reboot automatically. It will take 3 minutes to complete the upgrade procedure.