VA2409-MHU Firmware Update

Before Updating

Ensure you have:

- VA2409-MHU monitor with power adaptor.
- USB Type-C cable (included with the monitor).
- PC/laptop with Type-C interface. (Windows 10 or Windows 11 required.)

Setting Up the Monitor

1. Connect the power cord to the DC IN jack at the rear of the device.

2. Plug the power adapter into a power outlet.

3. Connect the monitor to the PC/laptop with the USB Type-C cable.

4. Power on the monitor and boot up the PC/laptop.

Setting Up the Firmware

1. Download the new firmware and put all the files into the same folder.

Name	Status	Type	Size
FLHubTool_V17.0.18.4	✓	Application	23,037 KB
Panther_FL7102_SC8102_Docking_V7.153....	✓	BIN File	17 KB
Read me	✓	Rich Text Format	10,339 KB

2. Open the **FLHubTool_ V17.0.18.4** application.

Name	Status	Type	Size
FLHubTool_V17.0.18.4	✓	Application	23,037 KB
Panther_FL7102_SC8102_Docking_V7.153....	✓	BIN File	17 KB
Read me	✓	Rich Text Format	10,339 KB

3. The words in the red box below will be black when the interface is successfully connected.

4. Click **GetVersion** to show the current version of the monitor.

5. Click **Update** and select the BIN file.

Name	Status	Type	Size
FLHubTool_V17.0.18.4		Application	23,037 KB
Panther_FL7102_SC8102_Docking_V7.153....		BIN File	17 KB
Read me		Rich Text Format	10,339 KB

6. Click **Open** to start the firmware update.

NOTE: Any interruptions during the firmware update process may permanently damage your monitor. Do not disconnect the USB cable or turn off your PC/laptop or monitor.

7. The prompt “Complete” will show onscreen when the update is finished.

8. Click **OK** and enjoy the updated VA2409-MHU.